





S,

SVC

NOT TO SCALE

## Ų SERVICE CONDUIT= 2'-R, 3' HORIZONTAL RADIUS BENDS

MAXIMUM COVER

3" SERVICE CONDUIT= 24" MIN. > NOT TO EXCEED 60" UNLESS OTHERWISE SPECIFIED BY PG&E.

ß II

ELECTRIC SERVICE

## LEGEND

-SV3-X -Sv3--PULL IN 4/OAL. 600V SERVICE CABLE IN 1-3" CUSTOMER INSTALLED SERVICE CONDUIT.

INSTALL 1-200 AMP METER.

EXISTING 17" X 30" SECONDARY SPLICE BOX

## NOTES

CUSTOMER TO TRENCH, BACKFILL AND INSTALL ALL SUBSTRUCTURES.

ALL PADS & ENCLOSURES MUST MEET REQUIREMENTS OUTLINED IN DOCUMENT 051122 REGARDING LOCATION CLEARANCES & MECHANICAL PROTECTION. CUSTOMER TO CALL PG&E FOR INSPECTION BEFORE BACKFILLING. TO SCHEDULE AN INSPECTION APPOINTMENT CALL (650) 598—7353.

TYPICAL SERVICE TRENCH

BEDDING MATERIAL

**4** Ŋ 30" IN FRANCHISE

18" ON RIVATE PROPERTY

AS REQUIRED



EST: KEN PEROTTI	
ADE: KEN PEROTTI	
SUPV: RONDA DeROSA	
REP: LORI RUSCA	]
PLNR:	L
SCALE: DATE:	
1"= 100'-0" 9-18-12	IPG

SUBSTRUCTURE **DRAWING** BAIR ISLAND AQUATIC CENTER

1402 MAPLE AV. REDWOOD CITY, SAN MATEO CO.

**PACIFIC** GAS AND **ELECTRIC** COMPANY

CO:	
SD:	
NOTIF.: 105984940	
OTHER:	
SHT: 1 0F 1	SHEETS
PM: 30948570	<b>REV.</b> 0

SECONDARY COVER 24" MIN.